



DOCUMENT GROUP: DATE: REVISION DATE:

CERAMIC/REPAIR/SYSTEMS 1ST FEBRUARY 2017 1ST FEBRUARY 2018 VERSION REF: VERSION NO: SUPERSEDES DATE: 11635/UPS236TUC 2.00 1ST NOVEMBER 2016

<u>MATERIAL SAFETY DATA SHEET</u> <u>UPS 236 TUC TOUGHENED POLYURETHANE CERAMIC KIT</u>

MANUFACTURER:

UNIQUE POLYMER SYSTEMS LTD, UNIT 19, LINK BUSINESS CENTRE, LINK WAY, MALVERN, WORCESTERSHIRE,

WR14 1UQ.

UNITED KINGDOM

TELEPHONE NUMBER: +44 (0) 1531 63 63 00

EMAIL: SALES@UNIQUEPOLYMERSYSTEMS.COM

EMERGENCY TELEHONE NUMBER: +44 (0) 1531 636300

THIS PRODUCT IS A KIT AND SUPPLIED AS A MULTI PART PRODUCT WHICH CONSISTS OF A BASE COMPONENT AND ACTIVATOR COMPONENT. THIS DOCUMENT CONTAINS THE MSDS FOR BOTH BASE AND ACTIVATOR COMPONENTS.

TRANSPORTATION INFORMATION

ACTIVATOR	BASE
(IMDG, IATA, ADR/RID).	(IMDG, IATA, ADR/RID).
UN number Not applicable.	UN number Not applicable.
UN proper shipping name -Not applicable.	UN proper shipping name -Not applicable.
No transport warning sign required.	No transport warning sign required.
Packing group Not applicable.	Packing group Not applicable.
Environmentally hazardous substance/marine	Environmentally hazardous substance/marine
pollutant	pollutant
No.	No.
Special precautions for user - Not applicable.	Special precautions for user - Not applicable.
Transport in bulk according to Annex II of	Transport in bulk according to Annex II of
MARPOL73/78 and the IBC Code	MARPOL73/78 and the IBC Code
Transport in bulk according to	Transport in bulk according to
Annex II of MARPOL 73/78	Annex II of MARPOL 73/78
and the IBC Code - Not applicable.	and the IBC Code - Not applicable.

DISCLAIMER: The information supplied in the MSDS is correct at the time of writing and date of issue. No warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for particular purpose or course of performance or usage of trade. The user of the material is responsible for ensuring the suitability of this product for application.

Unique Polymer Systems LTD Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00



SECTION 1: Identification of Substance/ Preparation and Company

1.1 Product identifier UPS 236 TUC TOUGHENED POLYURETHANE CERAMIC ACTIVATOR

- **1.2** Relevant identified uses of the substance or mixture and uses advised against Aliphatic polyamine hardener blend with inert fillers for repairing metalwork
- 1.3 Details of the supplier of the safety data sheet Unique Polymer Systems LTD, Unit 19, Link Business Centre, Link Way, Malvern, Worcestershire, WR14 1UQ United Kingdom Tel: +44 (0) 1531 63 63 00 Email: info@uniquepolymersystems.com
- 1.4 Emergency telephone number +44 (0) 1531 63 63 00 (9am to 5pm)

SECTION 2: Hazards Identification

SECTION 2: Hazards identification

2.1. Classification of the substance or mixtureClassificationPhysical hazards - Not ClassifiedHealth hazards - Not ClassifiedEnvironmental hazards - Not Classified

Classification (67/548/EEC or Xn;R20,R48/20. Carc. Cat. 3;R40. R42/43. Xi;R36/37/38. 1999/45/EC)

2.2. Label elements Pictogram



Signal word Danger Hazard statements H315 Causes skin irritation. H317 May cause an allergic skin reaction.

Unique Polymer Systems LTD



H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer by inhalation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements EUH204 Contains isocyanates. May produce an allergic reaction.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

Contains DIPHENYLMETHANE -4, 4'- DI-ISOCYANATE, Homopolymer of methylenediphenyl disocyanate, Isocyanic Acid, polymethylenepolyphenylene ester

Supplementary precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe vapour/spray.

P261 Avoid breathing vapour/spray.

P264 Wash contaminated skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P284 [In case of inadequate ventilation] wear respiratory protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in

a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P313 Get medical advice/attention.

P321 Specific treatment (see medical advice on this label).

P332+P313 If skin irritation occurs: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337 If eye irritation persists:

P362 Take off contaminated clothing.

P363 Wash contaminated clothing before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container to ...

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures Homopolymer of methylenediphenyl diisocyanate 30-60% CAS number: 39310-05-9

Unique Polymer Systems LTD



EC number: 500-297-1 REACH registration number: 01-2119457013-49-0000 Classification Acute Tox. 2 - H330 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Resp. Sens. 1 - H334 Skin Sens. 1 - H317 Carc. 2 - H351 STOT SE 3 - H335 STOT RE 2 - H373 Classification (67/548/EEC or 1999/45/EC) Xn;R20,R48/20. Carc. Cat. 3;R40. Xi;R36/37/38. R42/43.

Isocyanic Acid, polymethylenepolyphenylene ester 30-60% CAS number: 9016-87-9 Classification Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Resp. Sens. 1 - H334 Skin Sens. 1 - H317 Carc. 2 - H351 STOT SE 3 - H335 STOT RE 2 - H373 Classification (67/548/EEC or 1999/45/EC) Xn;R20,R48/20. Carc. Cat. 3;R40. Xi;R36/37/38. R42/43. DIPHENYLMETHANE -4, 4'- DI-ISOCYANATE 10-30% CAS number: 101-68-8 EC number: 202-966-0 Classification Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Resp. Sens. 1 - H334 E | REBUILD | ENHANCE Skin Sens. 1 - H317 Carc. 2 - H351 STOT SE 3 - H335 STOT RE 2 - H373 Classification (67/548/EEC or 1999/45/EC) Carc. Cat. 3;R40 Xn;R20,R48/20 Xi;R36/37/38 R42/43

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention immediately. Show this Safety Data Sheet to the medical personnel. Inhalation Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com



Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place. In the event of any sensitisation symptoms developing, ensure further exposure is avoided.

Ingestion Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.

Skin contact It is important to remove the substance from the skin immediately. In the event of any sensitisation symptoms developing, ensure further exposure is avoided. Remove

contamination with soap and water or recognised skin cleansing agent. Get medical attention if symptoms are severe or persist after washing.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue. If it is

suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contained breathing apparatus. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

4.2. Most important symptoms and effects, both acute and delayed

General information See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation May cause sensitisation or allergic reactions in sensitive individuals. A single exposure may cause the following adverse effects: Headache. Exhaustion and weakness. Prolonged or

repeated exposure may cause the following adverse effects: Suspected of causing cancer. Ingestion May cause sensitisation or allergic reactions in sensitive individuals. May cause irritation. Prolonged or repeated exposure may cause the following adverse effects: Suspected of causing cancer.

Skin contact May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to skin. Prolonged or repeated exposure may cause the following adverse effects: Suspected of causing cancer.

Eye contact Irritating to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry

powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. Unsuitable extinguishing

Unique Polymer Systems LTD



media

Do not use water jet as an extinguisher, as this will spread the fire. 5.2. Special hazards arising from the substance or mixture Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. This product is toxic. Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours. 5.3. Advice for firefighters Protective actions during firefighting Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Avoid inhalation of dust and vapours. Use suitable respiratory protection if ventilation is inadequate. Avoid contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the

aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills

immediately and dispose of waste safely. Provide adequate ventilation. Approach the spillage from upwind. Small Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labelled, sealed containers. Clean contaminated objects and areas thoroughly,

Unique Polymer Systems LTD



observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health

hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in

Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs.

Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Suspected of causing cancer. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

Advice on general

occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work the transmission of the toilet of the toilet.

work clothing daily before leaving workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in accordance with local regulations. Keep only in the original container. Keep container

tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent. Storage class Toxic storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters Occupational exposure limits Homopolymer of methylenediphenyl diisocyanate Long-term exposure limit (8-hour TWA): WEL 0.02 mg/m³ Short-term exposure limit (15-minute): WEL 0.07 mg/m³ Sen as NCO Isocyanic Acid, polymethylenepolyphenylene ester Long-term exposure limit (8-hour TWA): WEL 0.02 mg/m³ Short-term exposure limit (15-minute): WEL 0.07 mg/m³ Skin sensitiser.

Unique Polymer Systems LTD



as NCO

DIPHENYLMETHANE -4, 4'- DI-ISOCYANATE Long-term exposure limit (8-hour TWA): WEL 0,01 mg/m³ Short-term exposure limit (15-minute): WEL 0,07 mg/m³ as NCO Sen WEL = Workplace Exposure Limit Sen = Capable of causing occupational asthma. Homopolymer of methylenediphenyl diisocyanate (CAS: 39310-05-9) Ingredient comments EH40/2005 Workplace exposure limits. Medical supervision of all employees who come into contact with respiratory sensitisers is recommended. Personnel with a history of asthma-type conditions, bronchitis or skin sensitisation conditions should not work with MDI based products. The OELs listed do not apply to previously sensitised individuals. Sensitised individuals should be removed from any further exposure. Biological limit values Predicted Effect Levels: No PECs available, Predicted Effect Levels: No PECs available, Predicted Effect Levels: No PECs available Derivied Effect Levels: No DELs available Derivied Effect Levels: No DELs available Derivied Effect Levels: No DELs available 8.2. Exposure controls Protective equipment Appropriate engineering controls Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure. Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead. Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended. Other skin and body

protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

Hygiene measures Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When

Unique Polymer Systems LTD



using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product. Respiratory protection Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

Environmental exposure

controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties Appearance Liquid.

Colour Colourless.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity Reactivity There are no known reactivity hazards associated with this product. 10.2. Chemical stability Stability Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions. 10.3. Possibility of hazardous reactions Possibility of hazardous reactions No potentially hazardous reactions known. 10.4. Conditions to avoid Conditions to avoid There are no known conditions that are likely to result in a hazardous situation. 10.5. Incompatible materials Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation. 10.6. Hazardous decomposition products Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Unique Polymer Systems LTD



Acute toxicity - oral Notes (oral LD₅₀) Based on available data the classification criteria are not met. Acute toxicity - dermal Notes (dermal LD₅₀) Based on available data the classification criteria are not met. Acute toxicity - inhalation Notes (inhalation LC₅₀) Acute Tox. 4 - H332 Harmful if inhaled. ATE inhalation (gases ppm) 22,727.27 ATE inhalation (vapours mg/l) 55.56 ATE inhalation (dusts/mists mg/l) 1.5 Skin corrosion/irritation Animal data Irritating. Serious eye damage/irritation Serious eye damage/irritation Causes serious eye irritation. Respiratory sensitisation Respiratory sensitisation There is evidence that the product can cause respiratory hypersensitivity. Skin sensitisation Skin sensitisation May cause skin sensitisation or allergic reactions in sensitive individuals. Germ cell mutagenicity Genotoxicity - in vitro Based on available data the classification criteria are not met. Carcinogenicity Carcinogenicity Suspected of causing cancer. IARC carcinogenicity None of the ingredients are listed or exempt. Reproductive toxicity Reproductive toxicity - fertility Based on available data the classification criteria are not met. Reproductive toxicity development Based on available data the classification criteria are not met Specific target organ toxicity - single exposure STOT - single exposure STOT SE 3 - H335 May cause respiratory irritation. Target organs Respiratory system, lungs Specific target organ toxicity - repeated exposure STOT - repeated exposure STOT RE 2 - H373 May cause damage to organs through prolonged or repeated exposure. Aspiration hazard Aspiration hazard Based on available data the classification criteria are not met. General information May cause cancer after repeated exposure. Risk of cancer depends on duration and level of exposure. The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Inhalation May cause sensitisation or allergic reactions in sensitive individuals. A single exposure may cause the following adverse effects: Headache. Exhaustion and weakness. Ingestion May cause sensitisation or allergic reactions in sensitive individuals. May cause irritation. Skin contact May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to skin. Eye contact Irritating to eyes. Route of entry Ingestion Inhalation Skin and/or eye contact Target organs Respiratory system, lungs Medical considerations Skin disorders and allergies.

Unique Polymer Systems LTD



SECTION 12: Ecological Information

Ecotoxicity Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

Toxicity Based on available data the classification criteria are not met.

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility No data available.

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information The generation of waste should be minimised or avoided wherever possible. Reuse or recycle

products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods Dispose of surplus products and those that cannot be recycled via a licensed waste disposal

contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

INNOVATE | REBUILD | ENHANCE -

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID). 14.1. UN number Not applicable. 14.2. UN proper shipping name Not applicable. 14.3. Transport hazard class(es) No transport warning sign required. 14.4. Packing group Not applicable. 14.5. Environmental hazards Environmentally hazardous substance/marine pollutant No.

Unique Polymer Systems LTD



14.6. Special precautions for user
Not applicable.
14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
Transport in bulk according to
Annex II of MARPOL 73/78
and the IBC Code
Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture National regulations Health and Safety at Work etc. Act 1974 (as amended).
The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].
EH40/2005 Workplace exposure limits.

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Commission Regulation (EU) No 453/2010 of 20 May 2010.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Dangerous Preparations Directive 1999/45/EC.

Dangerous Substances Directive 67/548/EEC.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out. Inventories

EU - EINECS/ELINCS

None of the ingredients are listed or exempt.

SECTION 16: Other information

Classification procedures according to Regulation (EC) 1272/2008 Acute Tox. 4 - H332: STOT RE 2 - H373: STOT SE 3 - H335: Skin Irrit. 2 - H315: Eye Irrit. 2 -H319: Resp. Sens. 1 - H334: Skin Sens. 1 - H317: Carc. 2 - H351: : Calculation method. Training advice Read and follow manufacturer's recommendations. Only trained personnel should use this material. Revision date 16/05/2013 Risk phrases in full R20 Harmful by inhalation.

INNOVATE | REBUILD | ENHANCE

R36/37/38 Irritating to eyes, respiratory system and skin.

R40 Limited evidence of a carcinogenic effect.

R42/43 May cause sensitisation by inhalation and skin contact.

Unique Polymer Systems LTD



R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Hazard statements in full H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H351 Suspected of causing cancer by inhalation.

H373 May cause damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure if inhaled

DISCLAIMER: The information supplied in the MSDS is correct at the time of writing and date of issue. No warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for particular purpose or course of performance or usage of trade. The user of the material is responsible for ensuring the suitability of this product for application.



DISCLAIMER: The information supplied in the MSDS is correct at the time of writing and date of issue. No warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for particular purpose or course of performance or usage of trade. The user of the material is responsible for ensuring the suitability of this product for application.

SECTION 1: Identification of Substance/ Preparation and Company

- 1.2 Product identifier UPS 236 TUC TOUGHENED POLYURETHANE CERAMIC BASE
- 1.2 Relevant identified uses of the substance or mixture and uses advised against Aliphatic polyamine hardener blend with inert fillers for repairing metalwork

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com



- 1.3 Details of the supplier of the safety data sheet Unique Polymer Systems LTD, Unit 19, Link Business Centre, Link Way, Malvern, Worcestershire, WR14 1UQ United Kingdom Tel: +44 (0) 1531 63 63 00 Email: info@uniquepolymersystems.com
- 1.4 Emergency telephone number +44 (0) 1531 63 63 00 (9am to 5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture
Classification
Physical hazards Not Classified
Health hazards Not Classified
Environmental hazards Not Classified
Classification (67/548/EEC or
1999/45/EC)
N;R50/53.
2.2. Label elements
Hazard statements NC Not Classified
2.3. Other hazards
This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. Ingestion Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an

unconscious person. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. Skin contact Remove affected person from source of contamination. Rinse immediately with plenty of water.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue. 4.2. Most important symptoms and effects, both acute and delayed

General information See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may

Unique Polymer Systems LTD





be inhaled, resulting in the same symptoms as inhalation.
Skin contact Prolonged contact may cause dryness of the skin.
Eye contact May cause temporary eye irritation.
4.3. Indication of any immediate medical attention and special treatment needed Notes for the doctor Treat symptomatically.
Specific treatments No special treatment required.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Hazardous combustion

products

. Thermal decomposition or combustion products may include the following substances:

Harmful gases or vapours.

5.3. Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions, protective equipment and tangency proceedies

unnecessary and unprotected personnel away from the spillage. Wear protective clothing as

described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage.

6.2. Environmental precautions

Environmental precautions Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills

immediately and dispose of waste safely. Reuse or recycle products wherever possible.

Approach the spillage from upwind. Small Spillages: If the product is soluble in water, dilute

the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the

spillage with an inert, dry material and place it in a suitable waste disposal container. Large

Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent

treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other

non-combustible material. Place waste in labelled, sealed containers. Clean contaminated

objects and areas thoroughly, observing environmental regulations. Flush contaminated area

Unique Polymer Systems LTD



with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash

contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in accordance with local regulations.

Storage class Unspecified storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

8.2. Exposure controls Protective equipment

Appropriate engineering

controls

Provide adequate ventilation. Good general ventilation should be adequate to control worker exposure to airborne contaminants.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. The following protection should be worn: Chemical splash goggles.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended. Other skin and body

protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

Hygiene measures Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented.

Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke.

Respiratory protection Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Provide adequate ventilation. Large Spillages: If ventilation is inadequate, suitable respiratory protection must be worn.

Unique Polymer Systems LTD



Environmental exposure controls Not regarded as dangerous for the environment.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical propertiesAppearance Liquid.9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity Reactivity There are no known reactivity hazards associated with this product. 10.2. Chemical stability Stability Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions. 10.3. Possibility of hazardous reactions Possibility of hazardous reactions No potentially hazardous reactions known. 10.4. Conditions to avoid Conditions to avoid There are no known conditions that are likely to result in a hazardous situation. 10.5. Incompatible materials Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation. 10.6. Hazardous decomposition products Hazardous decomposition products Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects Toxicological effects Not regarded as a health hazard under current legislation. Acute toxicity - oral Notes (oral LD₅₀) Based on available data the classification criteria are not met. Acute toxicity - dermal Notes (dermal LD₅₀) Based on available data the classification criteria are not met. Acute toxicity - inhalation Notes (inhalation LC₅₀) Based on available data the classification criteria are not met. Skin corrosion/irritation Animal data Based on available data the classification criteria are not met. Serious eye damage/irritation Serious eye damage/irritation Based on available data the classification criteria are not met. Respiratory sensitisation Respiratory sensitisation Based on available data the classification criteria are not met. Skin sensitisation Skin sensitisation Based on available data the classification criteria are not met. Germ cell mutagenicity Genotoxicity - in vitro Based on available data the classification criteria are not met. Carcinogenicity Carcinogenicity Based on available data the classification criteria are not met. Unique Polymer Systems LTD



IARC carcinogenicity None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure. Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information No specific health hazards known. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.

Skin contact Prolonged contact may cause dryness of the skin.

Eye contact May cause temporary eye irritation.

Route of entry Ingestion Inhalation Skin and/or eye contact

Target organs No specific target organs known.

SECTION 12: Ecological Information

Ecotoxicity Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

Toxicity Based on available data the classification criteria are not met.

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility No data available.

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Disposal methods Dispose of surplus products and those that cannot be recycled via a licensed waste disposal

REBUILD | ENHANCI

contractor. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of the local water authority.

SECTION 14: Transport information

Unique Polymer Systems LTD



General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID). 14.1. UN number Not applicable. 14.2. UN proper shipping name Not applicable. 14.3. Transport hazard class(es) No transport warning sign required. 14.4. Packing group Not applicable. 14.5. Environmental hazards Environmentally hazardous substance/marine pollutant No. 14.6. Special precautions for user Not applicable. 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information



None of the ingredients are listed or exempt.

SECTION 16: Other information

Training advice Read and follow manufacturer's recommendations. Only trained personnel should use this material. Risk phrases in full NC Not classified.

R22 Harmful if swallowed.

R23 Toxic by inhalation.

R36/38 Irritating to eyes and skin.

R39 Danger of very serious irreversible effects.

R41 Risk of serious damage to eyes.

R48/25 Toxic: danger of serious damage to health by prolonged exposure if swallowed.

R50 Very toxic to aquatic organisms.

Unique Polymer Systems LTD



R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic


environment.

R60 May impair fertility.

R61 May cause harm to the unborn child.

R68 Possible risk of irreversible effects.

DISCLAIMER: The information supplied in the MSDS is correct at the time of writing and date of issue. No warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for particular purpose or course of performance or usage of trade. The user of the material is responsible for ensuring the suitability of this product for application.



Unique Polymer Systems LTD Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00